ASL – Area/Site/Roadway



FIXTURE CODE: ASL1&2	
PROJECT:	Control of the contro
CUSTOMER:	
NOTES:	

FEATURES & BENEFITS:

- The ASL fixture uses solid state / light emitting diode (LED) light source
- 12 VDC electronic dimming drivers
- Die cast aluminum housing
- Multiple light distributions available

SPECIFICATIONS:

OVERVIEW: The light fixture assembly is a Cobrahead style fixture and comes complete with LEDs and driver used to operate the fixture from the solar charged batteries. The light fixture can be mounted anywhere on the pole or wall below the solar, or can be mounted separately on another pole or wall, even in the shade.

APPLICATIONS: Roadways, Parking Lots, Area, Perimeters

HOUSING: Die Cast Aluminum

FINISH: Black, Bronze, Gray, White

OPTICAL ASSEMBLY: Each LED has an individual optical lens

LAMPING: ASL1 = 15 - 55 Watt LED / ASL2 = 60 - 110 Watt LED Type II, III, IV, V Distribution

DIMENSIONS: ASL1 = 11.7" Long x 11.7" Wide x 5.9" High / ASL2 = 22.4" Long x 11.7" Wide x 5.9" High

SHIPPING WEIGHT: 15 lbs / 19 lbs







Note: SEPCO™ reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice.

© 2012 SEPCO Solar Electric Power Company, All Rights Reserved • For more information visit our website: www.sepco-solarlighting.com• Printed in USA • TRVSPEC6/12