## CIM1 - Cimarron



FIXTURE CODE: CIM1	
PROJECT:	
CUSTOMER:	
NOTES:	

## **FEATURES & BENEFITS:**

- The Cimarron fixture uses solid state / light emitting diode (LED) light source
- 12 VDC electronic dimming drivers
- Die-cast aluminum housing with multiple pole and surface mounting configurations
- Multiple light distributions available

## SPECIFICATIONS:

OVERVIEW: The light fixture assembly is a shoebox style fixture and comes complete with LEDs and driver used to operate the fixture from the solar charged batteries. The light fixture can be mounted anywhere on the pole or wall below the solar, or can be mounted separately on another pole or wall, even in the shade.

APPLICATIONS: Roadways, Parking Lots, Area, Perimeters

HOUSING: Die Cast Aluminum

FINISH: Gray or Dark Bronze

OPTICAL ASSEMBLY: Each LED has an individual optical lens

LAMPING: 15 – 70 Watt LED Type II, III, IV, V Distribution (CIM2 is available in a higher wattage)

DIMENSIONS: 21.75" Long x 16" Wide x 6.75" High

SHIPPING WEIGHT: 38 lbs











Note: SEPCO™ reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice. © 2012 SEPCO Solar Electric Power Company, All Rights Reserved • For more information visit our website: www.sepco-solarlighting.com • Printed in USA • CIM1SPEC6/12